

# **YSL-2000HD**

1513

CHECK-LINE

MEM

## **Multi-Function Speed & Length Meter**

- Two slide-on measuring heads (included) make it simple to rapidly convert from one function to another.
- Accuracy of ± 0.02%.
- Built-in memory for last, maximum, minimum value.
- NIST Certification Included
- 5 Year Warranty

The CHECK-LINE YSL-2000HD combines the functions of three separate instruments in one, easy-to-use device.

It accurately measures the speed and length of yarns, and other filaments using a unique "wrapper" roller. This precision roller directs the filament onto the low-inertia, U-grooved measuring wheel to maximize contact and eliminate filament slip and breakage.

The YSL-2000HD also functions as a contact or non-contact tachometer to measure rotational speeds of shafts, motors, pulleys, etc. or linear speeds of moving surfaces such as conveyor belts, webs of paper or fabric, etc.



# **Specifications**

#### Measuring Ranges *RPM*

RPM	<i>Contact:</i> 1.00 - 99,999 rpm	
Surface Speed	0.30 – 6,500 feet/min 0.10 – 1,999 meters/min 4.0 – 78,000 inches/min	
Length	0.01 – 99,999 feet 0.02 – 99,999 meters 1.0 – 99,999 inches	
Resolution	0.01 from 0 – 100 0.1 from 100 – 1,000 1 from 1000 – 99,999	
Yarn/Wire Diameter (max.)	) Yarn: 1mm / Wire: 0.3mm	
Accuracy	±0.02% of reading or 1 digit	
Display	5-Digit LCD, .39" (10mm) high	
Decimal Point	Automatic	
Memory System	Maximum, minimum, and last reading (retained in memory for the life of the batteries)	
Measurement System	Non-Contact:Visible LED light beamContact:Contact adapter	
Sensing Distance	Up to 14 inches (350mm)	
Display Update Time	0.5 seconds or one measuring	
Auto Power Off	After 30 seconds of non-use (minimum, maximum and last reading retained in memory)	
Battery Life	20 hours continuous use	
Weight	6 ounces (170 grams)	
Housing Material	ABS Plastic	
Operating Temperature	32 to 122° F (0 to 50° C)	
Storage Temperature	-4 to 150° F (-20 to 70° C)	
Optional Accessories	Shaft extension, 3.15 inches (80 mm)	
Warranty	5 years	

Non-Contact: 1 00 - 99 999 rpm

## Engineering Units (selectable)

Linear Speed	Length	Revolutions
feet/min meters/min inches/min	feet meters inches	rpm

### **Tachometer Accessories**

Model DTFA



Model DTCA



12" Measuring Wheel Model LMA-3





Reflcective Tape Model CDT-TAPE

#### **Complete Kit**

Model DT6

The YSL unit, two slide-on measuring heads (tachometer and yarn speed), cone tip, universal surface speed wheel with integrated funnel tip adapter, reflective tape, two AA batteries and operating instructions, all supplied in a foam-fitted, hard-plastic carrying case.





#### Power Tech International Group sales@powertech-group.com www.powertech-group.com